

ISM ANTENNA

Antenna ISM Connector Mount SMVS, 169 MHz, 0 dBi, SMA(m)

AO-A169-SMVS

SECTRON company offers a wide portfolio of ISM antennas with various versions differing in shape, level of gain and manner of attachment. SECTRON guarantees a compatible connection between an antenna and all antenna adaptors produced by SECTRON.


BENEFITS

- Low VSWR
- Easy installation
- Omnidirectional radiation pattern

FEATURES AO-A169-SMVS


Technology	ISM	
Frequency bands	169 MHz	
Bandwidth	<7 MHz	
Gain	0 dBi	
VSWR	<2.0:1	
Impedance	50 Ohm	
Directivity	Omnidirectional	
Beam angle	360°H/50°V	
Polarization	Linear	
Maximum input power	10 W	
Power voltage	-	
Dimensions	Ø12.7 x 120 mm	
Weight	5.34 g	
Operating temperature	-30 to +80 °C	
Execution	External	
Method of attachment	Connector mount	
Cable type	-	
The cable length	-	
Connector type	SMA(m)	
Certification	RoHS, ISO9001, ISO14001	

DRAWING




MEASURED GRAPHS AO-A169-SMVS

 S_{11} - Return Loss [dB]



VSWR - Voltage standing wave ratio [-]



SUMMARY

Frequency [MHz]	S_{11} [dB]	VSWR [-]
166	-19.45	1.64
169	-17.40	2.18
172	-11.09	2.83

VARIANTS

Different connector variants or cable lengths are available on request.

CONTACTS

SECTRON s.r.o. Josefa Šavla 1271/12 709 00 Ostrava 9, Czech Republic

WWW.SECTRON.CZ Tel.: +420 556 621 020