

Antenna IoT B GLONASS & Bluetooth RFID & G S Router & Antenna IoT Ante Antenna IoT B GLONASS UMTS B Antenna Java Modem GLONASS & oden Bluetooth M2M O LTE F Rout

LTE ANTENNA

Antenna LTE Flexible 142, 3 dBi, IPEX MHF, 1.13mm/10cm

AO-ALTE-G142I100

SECTRON company offers a wide portfolio of LTE antennas with various versions differing in shape, level of gain and manner of attachment. SECTRON guarantees a compatible connection between an antenna and all antenna adaptors produced by SECTRON.




BENEFITS

- Minimalistic dimensions
- Flexible

Technology	LTE
Frequency bands	700/800/900/1700/2400/2600 MHz
Bandwidth	-
Gain	3 dBi
VSWR	<3.0:1
Impedance	50 Ohm
Directivity	Directional
Beam angle	H 30° V 180°
Polarization	Linear
Maximum input power	10 W
Power voltage	-
Dimensions	110 x 20 mm
Weight	-
Operating temperature	-40 to +85 °C
Execution	External
Method of attachment	Adhesive
Cable type	Hirose 068
The cable length	100 mm
Connector type	IPEX MHF

DRAWING



Different connector variants or cable lengths are available on request.

CONTACTS