

KEY FEATURES

220 Channels for multi-constellation GNSS support

Fully EMI shielded module

Advanced kalman filter PVT engine

Compact design for mobile applications

Flexible RS232, USB and ethernet interfacing

L1 RTK centimeter level position accuracy

Proven Trimble Maxwell 6 technology

Supports FDE and RAIM

SINGLE FREQUENCY GPS/GLONASS/GALILEO/BEIDOU RECEIVER DELIVERS HIGHEST ACCURACY FOR MOBILE POSITIONING APPLICATIONS

THE LATEST IN GNSS TECHNOLOGY FROM TRIMBLE IS NOW AVAILABLE TO ORIGINAL EQUIPMENT MANUFACTURERS (OEM) AND SYSTEM INTEGRATORS.

COMPACT FULL METAL JACKET DESIGN

The Trimble® BD910 GNSS receiver module has been designed for applications requiring high accuracy from multiple GNSS constellations in a very small package. Mobile platforms can now embed proven Trimble RTK technology using a shielded module in a compact 41 mm x 41 mm x 7 mm form factor. The Trimble BD910 is a complete drop-in, solder-down module manufactured and tested to Trimble's highest quality standards. This design ensures the high quality GNSS signals are protected from the sources of EMI on the host platform. It also significantly reduces radiated emissions which speeds compliance certification and time to market.

MULTI CONSTELLATION GNSS

The Trimble BD910 supports the L1 frequency from the GPS, GLONASS, Galileo, and BeiDou constellations. An L1 RTK engine delivers 1–2 centimeter positions. For applications that do not require centimeter accuracy the BD910 contains an advanced kalman filter PVT engine that delivers high accuracy GNSS, DGNSS positions in the most challenging environments such as urban canyons. Different configurations of the module are available from SBAS to multi-constellation L1 RTK. All features are password-upgradeable, allowing functionality to be upgraded as your requirements change.

The receiver also supports Fault Detection and Exclusion (FDE) and Receiver Autonomous Integrity Monitoring (RAIM) for safety-critical applications.

DEMONSTRATED PERFORMANCE

Industry professionals trust Trimble embedded positioning technologies as the core of their precision applications. With the latest Trimble-precise Maxwell™ 6 technology, the BD910 provides assurance of long-term future-proofing and trouble-free operation. Moving the industry forward, the Trimble BD910 redefines high-performance positioning:

- On-board multipath mitigation
- Proven low-elevation tracking technology

FLEXIBLE INTERFACING

The Trimble BD910 was designed for easy integration and rugged dependability. Customers benefit from the Ethernet connectivity available on the board, allowing high speed data transfer and configuration via standard web browsers. USB and RS-232 are also supported. Just like other Trimble embedded technologies, easy to use software commands simplify integration and reduce development times.



BD910 GNSS RECEIVER

TRIMBLE BD910 GNSS RECEIVER MODULE

TECHNICAL SPECIFICATIONS¹

- 220 Channels:
 - GPS: L1 C/A
 - GLONASS: L1 C/A
 - Galileo: E1²
 - BeiDou: B1
 - QZSS: L1 C/A, L1 SAIF
 - SBAS: L1 C/A
- Advanced Trimble Maxwell 6 Custom Survey GNSS Technology
- High precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- 1 USB 2.0 Device port
- 1 LAN Ethernet port:
 - Supports links to 10BaseT/100BaseT auto-negotiate networks
 - All functions are performed through a single IP address simultaneously—including web GUI access and raw data streaming
 - Network Protocols supported
 - ▶ HTTP (web GUI)
 - ▶ NTP Server
 - ▶ NMEA, GSOFF, CMR over TCP/IP or UDP
 - ▶ NTripCaster, NTripServer, NTripClient
 - ▶ mDNS/uPnP Service discovery
 - ▶ Dynamic DNS
 - ▶ eMail alerts
 - ▶ Network link to Google Earth
 - ▶ Support for external modems via PPP
- 4 x RS232 ports
 - Baud rates up to 115,200
- Up to 20 Hz raw measurement & position outputs
- Reference outputs/inputs . . . CMR, CMR+, sCMRx, RTCM 2.1, 2.2, 2.3, 3.0, 3.1¹²
- Navigation outputs ASCII: NMEA-0183 GSV, AVR, RMC, HDT, V GK, VHD, ROT, G GK, GGA, GSA, ZDA, VTG, GST, PJT, PJK, BPQ, GLL, GRS, GBS and Binary: Trimble GSOFF
- Control Software: HTML web browser, Internet Explorer, Firefox, Safari, Opera, Google Chrome
- 1 Pulse Per Second Output
- Event Marker Input Support
- Supports Fault Detection & Exclusion (FDE), Receiver Autonomous Integrity Monitoring (RAIM)

POSITIONING SPECIFICATIONS³

Mode	Accuracy ⁴	Latency ⁵	Maximum Rate
Single Baseline RTK (<5 km)	0.008 m + 1 ppm Horizontal	<30 ms	20 Hz
	0.015 m + 1 ppm Vertical		
DGNS	0.25 m + 1 ppm Horizontal	<20 ms	20 Hz
	0.50 m + 1 ppm Vertical		
SBAS ⁷	0.50 m Horizontal	<20 ms	20 Hz
	0.85 m Vertical		

RTK initialization time³ typically <1 minute
 RTK initialization reliability³ >99.9%

PERFORMANCE SPECIFICATIONS

- Time to First Fix (TTFF)⁷
 - Cold Start⁸ <45 seconds
 - Warm Start⁹ <30 seconds
 - Signal Re-acquisition <2 seconds
- Velocity Accuracy^{3,4}
 - Horizontal 0.007 m/sec
 - Vertical 0.020 m/sec
- Acceleration 11 g
- Maximum Operating Limits¹⁰
 - Velocity 515 m/sec
 - Altitude 18,000 m

PHYSICAL AND ELECTRICAL CHARACTERISTICS

- Size 41 mm x 41 mm x 7 mm
- Power 3.3 V DC +5%/–3%
 Typical 1.1 W (L1 GPS + L1 GLONASS)
- Weight 19 grams
- Connectors
 - I/O 80 pin Narrow Pitch Panasonic Socket
 - Antenna MMCX receptacle
- Antenna LNA Power Input
 - Input voltage 3.3 V DC to 5 V DC
 - Maximum current 400 mA
- Minimum required LNA Gain 24.5 dB

ENVIRONMENTAL CHARACTERISTICS¹¹

- Temperature
 - Operating –40 °C to +85 °C
 - Storage –55 °C to +85 °C
- Vibration MIL810F, tailored
 Random 6.2 gRMS operating
 Random 8 gRMS survival
- Mechanical shock MIL810D
 ±40 g operating
 ±75 g survival
- Operating Humidity 5% to 95% R.H. non-condensing, at +60 °C

ORDERING INFORMATION

- Module Trimble BD910 GNSS available in a variety of configurations from SBAS upwards
- Evaluation Kit Includes interface board and power supply

1 Trimble BD910 is available in a variety of software configurations. Specifications shown reflect full capability.
 2 Developed under a License of the European Union and the European Space Agency.
 3 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
 4 1 sigma level, when using Trimble Zephyr 2 antennas.
 5 At maximum output rate.
 6 GPS only and depends on SBAS System performance. FAA WAAS accuracy specifications are <5 m 3DRMS.
 7 Typical observed values.
 8 No previous satellite (ephemerides / almanac) or position (approximate position or time) information.
 9 Ephemerides and last used position known
 10 As required by the U.S. Department of Commerce to comply with export licensing restrictions.
 11 Dependent on appropriate mounting/enclosure design.
 12 Input only network correction

Specifications subject to change without notice.

© 2014, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. (08114)



AMERICAS
 TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 510 DeGuigne Drive
 Sunnyvale, CA 94085 USA
 +1-408-481-8000 Phone
 Email: americasales@trimble.com

EUROPE & MIDDLE EAST
 TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 Germany
 +49 (6142) 177-2135 Phone
 France
 +33 2 28 09 3800 Phone
 Email: emeasales-intech@trimble.com

CHINA
 TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 311 Fute (M) Road, 3F
 Wai Gaoqiao Free Trade Zone
 Pudong, Shanghai 200131 China
 Email: chinasales-intech@trimble.com

ASIA - PACIFIC
 TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 Email: asiasales-intech@trimble.com

RUSSIA
 TRIMBLE NAVIGATION LIMITED
 Integrated Technologies
 +49 (6142) 177-2135 Phone
 Email: rusales-intech@trimble.com